

# Instruction for Vector Optics Hugo 3-12x44GT Rifle Scope



**WARNING:** NEVER LOOK AT THE SUN THROUGH THE RIFLESCOPE (OR ANY OTHER OPTICAL INSTRUMENT). IT MAY PERMANENTLY DAMAGE YOUR EYES.

## EYEPIECE FOCUSING

The eyepiece is designed to provide a precise fast focus at certain eye relief. The eyepiece will focus faster than your eye can compensate for any inaccuracy in your adjustment.

## MOUNTING

The rifle scope is installed on gun by means of a pair of weaver or dovetail mount rings. Use qualified mount with base designed to fit your particular rifle. The rifle scope shall be mounted as low as possible without touching either the barrel or the receiver. For safety reasons, allow at least 3 inches of clearance between the rifle scope and your eyes when shooting. Slide rifle scope forward or backward to acquire the proper eye relief that allows you to see full field of view. Rotate the rifle scope in the rings that the vertical crosshair is vertical and horizontal crosshair is horizontal. Then tighten all screws to fix rifle scope firmly on the rifle.

Don't exceed 16 inch / pounds of torque on the ring's screws.

## ZEROING

Hugo 3-12x44GT rifle scope features audible click elevation and windage adjustments. Elevation is the vertical (up-and-down) adjustment, usually on the top of the rifle scope. Windage is the horizontal (left-to-right) adjustment, usually on the right of the rifle scope.

The scope features 1/4 M.O.A (Minute of Angle) windage and elevation adjustment with audible clicks, meaning that 1 click moves the point of impact 1/4 inch at 100 yards.

With the rifle scope mounted, rest the firearm onto a solid support and aim at a target 100 yards away. Slowly shoot a small 3 to 5 rounds test group onto your target. Adjust windage & elevation screws in the direction you want to move the bullet impact. Each click of adjustment moves the point of impact. Shoot another 3 to 5 rounds test group. Repeat until you are satisfied with the point of aim.

## VARIABLE MAGNIFICATION ADJUSTMENTS

To change magnification, simply rotate the Power Selector Ring to achieve the designed power with index dot.

Generally speaking, lowest power to have the widest field of view for quick shots at close range. Higher power should be reserved for precise long-range shots.

## PARALLAX SETTING

Parallax is a condition that occurs when the image of the target is not focused precisely on the reticle plane. Parallax is visible as an apparent movement between the reticle and the target. This side wheel parallax is designed for permission of precise focusing, while simultaneously readjusting the parallax free distance, for any range from 10 yards to infinity. One can look through the optical sight and turn the side focus ring until the target, at whatever range, is sharply focused. This feature makes the highly accurate side winder range of riflescopes ideal for both hunting and target purposes.

## TURNING ON & ADJUSTING THE BRIGHTNESS LEVEL

Located on the upper of the riflescope ocular lens, controls the reticle illumination. There are 11 brightness levels red and 1 level NV for Hugo 3-12x44GT riflescope.

Rotate the switch will turn the illumination on. Simply turn the switch to adjust the brightness level of the reticle.

You can increase the brightness level to #11, which is the highest setting. Set the switch to 0 will turn the illumination off.

## BATTERY EXCHANGE

Your riflescope illumination is powered by 1 pc CR2032 button battery. Should the illumination grow dim or not turn on, you will need to exchange the battery. To exchange battery, use the proper screw driver to release the battery compartment cover. Remove the used battery, insert the new one. Screw on the cover again.

## SEALED, WATERPROOF AND FOGPROOF

The riflescope is nitrogen-purged to remove any vestige of internal moisture, also has O-ring to prevent the entry of dust or moisture.

## MAINTENANCE

Your riflescope, though amazingly tough, is a precision instrument that deserves reasonable cautious care.

- When cleaning the lens, first blow away any dirt and dust, or use a soft lens brush. Fingerprints and lubricants can be wiped off with lens tissue, or a soft clean cotton cloth, moistened with lens cleaning fluid.
- All moving parts of the riflescope are permanently lubricated. Do not try to lubricate them.
- No maintenance is needed on the riflescope's outer surface, except to occasionally wipe off dirt or fingerprints with a soft cloth.
- Use lens covers whenever convenient.

## STORAGE

Avoid storing the riflescope in hot places, such as the passenger compartments of vehicles on hot days. The high temperatures could adversely affect the lubricants and sealants. A vehicle's trunk, a gun cabinet or a closet is preferable. Never leave the riflescope where direct sunlight can enter either the objective lens.

Damage may result from the concentration (burning glass effect) of the sun's rays.

For More details please visit our website: [www.vectoroptics.com](http://www.vectoroptics.com)

# VECTOR OPTICS



## VOI-10BDC Reticle Pattern

